

Översikt



- ▲ RS-485 Interface
- ▲ Stöder Modbus RTU / ASCII
- ▲ LED Indikeringar
- ▲ Isolationsspänning: 5000 V DC
- ▲ Bred driftstemperatur: -20 ~ +75 °C
- ▲ Dubbel watchdog timer
- ▲ EFT and ESD protection
- ▲ Fri PC mjukvara "Yotta Utility"

Tekniska specifikationer

Type	A-1057	A-1058	A-1068	A-1069	A-1051	A-1055	A-1055S	A-1060
Utgångar	12	12	8	8	--	8	8	4
Ingångar	--				16	8	8	8
Spänningsförbrukning	Nearly 24VDC 0.96W	Nearly 24VDC 0.96W	Nearly 24VDC 1.68W	Nearly 24VDC 2.88W	Nearly 24VDC 1.66W	Nearly 24VDC 1.28W	Nearly 24VDC 1.28W	Nearly 24VDC 2.26W
Spänningsmatning	+10 ~ +30 VDC							
Utgångs typ	PNP	NPN	Signal Relä	Kraft Relä	--	NPN	PNP	Kraft Relä
Ingångstyp	--				Isolerad digital			
Max utgångsbelastning	10 - 35 VDC/1A	40VDC /200mA	120VAC /0.5A 30VDC/1A	250VAC /5A 30VDC/1A	--	40VDC /200mA	10-35VDC/1A	250VAC /5A 30VDC/1A
Ingångs-nivå (Isolation)	--				- Logic level 0: +1 V max. - Logic level 1: +3.5 ~ 30 V			
Isolationsspänning	5000 V DC							
LED	Ja							
Modbus Support	Modbus RTU + Modbus ASCII							
Watchdog Timer	System m & Comm.							

